


橡胶挡圈DR-1



(美国标准AS568A)



O形圈 编号	d1	b	h	O形圈 编号	d1	b	h	O形圈 编号	d1	b	h	O形圈 编号	d1	b	h
4	2.44	1.35	1.24	47	114.76	1.35	1.24	141	59.21	2.18	1.35	206	13.16	3	1.02
5	3.23	1.35	1.24	48	121.11	1.35	1.24	142	60.78	2.18	1.35	207	14.73	3	1.02
6	3.56	1.35	1.24	49	127.46	1.35	1.24	143	62.38	2.18	1.35	208	16.33	3	1.02
7	4.34	1.35	1.24	50	133.81	1.35	1.24	144	63.96	2.18	1.35	209	17.91	3	1.02
8	5.13	1.35	1.24	102	1.96	2.18	1.35	145	65.56	2.18	1.35	210	19.46	3	1.02
9	5.94	1.35	1.24	103	2.77	2.18	1.35	146	67.13	2.18	1.35	211	21.03	3	1.02
10	6.73	1.35	1.24	104	3.56	2.18	1.35	147	68.73	2.18	1.35	212	22.63	3	1.02
11	8.31	1.35	1.24	105	4.34	2.18	1.35	148	70.31	2.18	1.35	213	24.21	3	1.02
12	9.91	1.35	1.24	106	5.13	2.18	1.35	149	71.91	2.18	1.35	214	25.81	3	1.02
13	11.56	1.35	1.24	107	5.94	2.18	1.35	150	73.48	2.18	1.35	215	27.38	3	1.02
14	13.16	1.35	1.24	108	6.73	2.18	1.35	151	76.66	2.18	1.35	216	28.98	3	1.02
15	14.73	1.35	1.24	109	8.31	2.18	1.35	152	83.01	2.18	1.35	217	30.56	3	1.02
16	16.33	1.35	1.24	110	9.91	2.18	1.35	153	89.36	2.18	1.35	218	32.16	3	1.02
17	17.91	1.35	1.24	111	11.48	2.18	1.35	154	95.71	2.18	1.35	219	33.88	3	1.02
18	19.51	1.35	1.24	112	13.08	2.18	1.35	155	102.06	2.18	1.35	220	35.48	3	1.02
19	21.08	1.35	1.24	113	14.66	2.18	1.35	156	108.41	2.18	1.35	221	37.06	3	1.02
20	22.68	1.35	1.24	114	16.26	2.18	1.35	157	114.76	2.18	1.35	222	38.66	3	1.02
21	24.26	1.35	1.24	115	17.83	2.18	1.35	158	121.11	2.18	1.35	223	41.83	3	1.02
22	25.86	1.35	1.24	116	19.43	2.18	1.35	159	127.46	2.18	1.35	224	45.01	3	1.02
23	27.43	1.35	1.24	117	21.11	2.18	1.35	160	133.81	2.18	1.35	225	48.18	3	1.02
24	29.03	1.35	1.24	118	22.68	2.18	1.35	161	140.16	2.18	1.35	226	51.36	3	1.02
25	30.61	1.35	1.24	119	24.28	2.18	1.35	162	146.51	2.18	1.35	227	54.53	3	1.02
26	32.21	1.35	1.24	120	25.86	2.18	1.35	163	152.86	2.18	1.35	228	57.71	3	1.02
27	33.78	1.35	1.24	121	27.46	2.18	1.35	164	159.21	2.18	1.35	229	60.88	3	1.02
28	35.38	1.35	1.24	122	29.03	2.18	1.35	165	165.56	2.18	1.35	230	64.06	3	1.02
29	38.56	1.35	1.24	123	30.63	2.18	1.35	166	171.91	2.18	1.35	231	66.83	3	1.02
30	41.73	1.35	1.24	124	32.21	2.18	1.35	167	178.26	2.18	1.35	232	70	3	1.02
31	44.91	1.35	1.24	125	33.81	2.18	1.35	168	184.61	2.18	1.35	233	73.18	3	1.02
32	48.08	1.35	1.24	126	35.38	2.18	1.35	169	190.96	2.18	1.35	234	76.35	3	1.02
33	51.26	1.35	1.24	127	36.98	2.18	1.35	170	197.31	2.18	1.35	235	79.53	3	1.02
34	54.43	1.35	1.24	128	38.56	2.18	1.35	171	203.66	2.18	1.35	236	82.7	3	1.02
35	57.61	1.35	1.24	129	40.16	2.18	1.35	172	210.01	2.18	1.35	237	85.88	3	1.02
36	60.78	1.35	1.24	130	41.73	2.18	1.35	173	216.36	2.18	1.35	238	89.05	3	1.02
37	63.96	1.35	1.24	131	43.33	2.18	1.35	174	222.71	2.18	1.35	239	92.23	3	1.02
38	67.13	1.35	1.24	132	44.91	2.18	1.35	175	229.06	2.18	1.35	240	95.4	3	1.02
39	70.31	1.35	1.24	133	46.51	2.18	1.35	176	235.41	2.18	1.35	241	98.58	3	1.02
40	73.48	1.35	1.24	134	48.08	2.18	1.35	177	241.76	2.18	1.35	242	101.75	3	1.02
41	76.66	1.35	1.24	135	49.68	2.18	1.35	178	248.11	2.18	1.35	243	104.93	3	1.02
42	83.01	1.35	1.24	136	51.26	2.18	1.35	201	5.13	3	1.02	244	108.1	3	1.02
43	89.36	1.35	1.24	137	52.86	2.18	1.35	202	6.73	3	1.02	245	111.28	3	1.02
44	95.71	1.35	1.24	138	54.43	2.18	1.35	203	8.31	3	1.02	246	114.45	3	1.02
45	102.06	1.35	1.24	139	56.03	2.18	1.35	204	9.91	3	1.02	247	117.63	3	1.02
46	108.41	1.35	1.24	140	57.61	2.18	1.35	205	11.56	3	1.02	248	121.11	3	1.02

橡胶挡圈DR-1  (美国标准AS568A)



O形圈 编号	d1	b	h	O形圈 编号	d1	b	h	O形圈 编号	d1	b	h	O形圈 编号	d1	b	h
249	124.28	3	1.02	316	22.56	4.65	1.93	354	130.89	4.65	1.93	426	118.77	5.99	2.97
250	127.46	3	1.02	317	24.13	4.65	1.93	355	134.06	4.65	1.93	427	121.95	5.99	2.97
251	130.63	3	1.02	318	25.73	4.65	1.93	356	137.24	4.65	1.93	428	125.12	5.99	2.97
252	133.81	3	1.02	319	27.31	4.65	1.93	357	140.41	4.65	1.93	429	128.3	5.99	2.97
253	136.98	3	1.02	320	28.91	4.65	1.93	358	143.59	4.65	1.93	430	131.47	5.99	2.97
254	140.16	3	1.02	321	30.48	4.65	1.93	359	146.76	4.65	1.93	431	134.65	5.99	2.97
255	143.33	3	1.02	322	32.08	4.65	1.93	360	149.94	4.65	1.93	432	137.82	5.99	2.97
256	146.51	3	1.02	323	33.43	4.65	1.93	361	153.11	4.65	1.93	433	141	5.99	2.97
257	149.68	3	1.02	324	35.26	4.65	1.93	362	159.46	4.65	1.93	434	144.17	5.99	2.97
258	152.86	3	1.02	325	38.43	4.65	1.93	363	165.81	4.65	1.93	435	147.35	5.99	2.97
259	159.21	3	1.02	326	41.61	4.65	1.93	364	172.16	4.65	1.93	436	150.52	5.99	2.97
260	165.56	3	1.02	327	44.78	4.65	1.93	365	178.51	4.65	1.93	437	153.7	5.99	2.97
261	171.91	3	1.02	328	47.96	4.65	1.93	366	184.86	4.65	1.93	438	159.36	5.99	2.97
262	178.26	3	1.02	329	51.13	4.65	1.93	367	191.21	4.65	1.93	439	165.71	5.99	2.97
263	184.61	3	1.02	330	54.31	4.65	1.93	368	197.56	4.65	1.93	440	172.06	5.99	2.97
264	190.96	3	1.02	331	57.61	4.65	1.93	369	203.91	4.65	1.93	441	178.41	5.99	2.97
265	197.31	3	1.02	332	60.78	4.65	1.93	370	210.26	4.65	1.93	442	184.76	5.99	2.97
266	203.66	3	1.02	333	63.96	4.65	1.93	371	216.61	4.65	1.93	443	191.11	5.99	2.97
267	210.01	3	1.02	334	67.13	4.65	1.93	372	222.96	4.65	1.93	444	197.46	5.99	2.97
268	216.36	3	1.02	335	70.31	4.65	1.93	373	229.31	4.65	1.93	445	203.81	5.99	2.97
269	222.71	3	1.02	336	73.48	4.65	1.93	374	235.66	4.65	1.93	446	216.51	5.99	2.97
270	229.06	3	1.02	337	76.66	4.65	1.93	375	242.01	4.65	1.93	447	229.21	5.99	2.97
271	235.41	3	1.02	338	79.83	4.65	1.93	376	248.36	4.65	1.93	448	241.91	5.99	2.97
272	241.76	3	1.02	339	83.13	4.65	1.93	377	254.71	4.65	1.93	449	254.61	5.99	2.97
273	248.11	3	1.02	340	86.31	4.65	1.93	378	267.41	4.65	1.93	450	267.31	5.99	2.97
274	254.46	3	1.02	341	89.48	4.65	1.93	379	280.11	4.65	1.93	451	280.01	5.99	2.97
275	267.16	3	1.02	342	92.66	4.65	1.93	380	292.81	4.65	1.93	452	292.71	5.99	2.97
276	279.86	3	1.02	343	95.83	4.65	1.93	381	305.51	4.65	1.93	453	305.41	5.99	2.97
277	292.56	3	1.02	344	99.01	4.65	1.93	382	330.91	4.65	1.93	454	318.11	5.99	2.97
278	305.26	3	1.02	345	102.31	4.65	1.93	383	356.31	4.65	1.93	455	330.81	5.99	2.97
279	330.66	3	1.02	341	89.48	4.65	1.93	384	381.71	4.65	1.93	456	343.51	5.99	2.97
280	356.06	3	1.02	342	92.66	4.65	1.93	385	406.6	4.65	1.93	457	356.21	5.99	2.97
281	381.46	3	1.02	343	95.83	4.65	1.93	386	432	4.65	1.93	458	368.91	5.99	2.97
282	406.12	3	1.02	344	99.01	4.65	1.93	387	457.4	4.65	1.93	459	381.61	5.99	2.97
283	431.52	3	1.02	345	102.31	4.65	1.93	388	482.75	4.65	1.93	460	394.31	5.99	2.97
284	456.92	3	1.02	346	105.49	4.65	1.93	389	508.15	4.65	1.93	461	406.5	5.99	2.97
309	11.43	4.65	1.93	347	108.66	4.65	1.93	390	533.55	4.65	1.93	462	419.2	5.99	2.97
310	13.06	4.65	1.93	348	111.84	4.65	1.93	391	558.95	4.65	1.93	463	431.9	5.99	2.97
311	14.61	4.65	1.93	349	115.01	4.65	1.93	392	584.02	4.65	1.93	464	444.6	5.99	2.97
312	16.21	4.65	1.93	350	118.19	4.65	1.93	393	609.42	4.65	1.93	465	457.3	5.99	2.97
313	17.78	4.65	1.93	351	121.36	4.65	1.93	394	634.82	4.65	1.93	466	470	5.99	2.97
314	19.38	4.65	1.93	352	124.54	4.65	1.93	395	660.22	4.65	1.93	467	482.7	5.99	2.97
315	20.96	4.65	1.93	353	127.71	4.65	1.93	425	115.6	5.99	2.97	468	495.4	5.99	2.97

橡胶挡圈DR-1



(美国标准AS568A)



O形圈 编号	d1	b	h	O形圈 编号	d1	b	h	O形圈 编号	d1	b	h	O形圈 编号	d1	b	h
469	508.1	5.99	2.97	902	6.77	1.22	1.14	910	19.98	1.97	1.35	924	44.48	2.4	1.65
470	533.5	5.99	2.97	903	8.35	1.22	1.14	911	22.72	2.36	1.62	928	53.89	2.4	1.65
471	558.9	5.99	2.97	904	9.62	1.37	1.28	912	24.27	2.36	1.62	932	60.16	2.4	1.65
472	584.3	5.99	2.97	905	11.22	1.37	1.28	913	25.84	2.36	1.62				
473	609.7	5.99	2.97	906	12.59	1.49	1.39	914	27.4	2.36	1.62				
474	635.1	5.99	2.97	907	14.27	1.66	1.22	916	30.55	2.36	1.62				
475	660.5	5.99	2.97	908	17.16	1.77	1.22	918	35.22	2.36	1.62				
901	5.4	1.07	0.99	909	18.74	1.97	1.35	920	38.26	2.4	1.65				