

# 不锈钢四氟油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点							
VA	不锈钢四氟油封		不锈钢+四氟	≤1	-70至260	≤40	具抗磨性，耐腐蚀， 适用高温，高速，高压 工况和润滑不良工况							
d	D	H	d	D	H	d	D	H	d	D	H	d	D	H
20	40	11	25	42	7	40	52	7	50	72	6	70	90	10
30	50	11	25	42	8	40	55	8	50	72	12	70	95	8
35	55	11	25	45	8	40	55	10	51	70	10	72	88	10
40	62	11	25.4	41.4	10.16	40	56	7	52	70	8	74	102	9.5
42	65	12	27	47.6	6.5	40	60	8	52	73	10	75	93	8
45	68	12	28	42	6	40	62	8	54	73	10	75	100	8
50	72	12	28	45	10	41.2	54	8	55	70	8	76	101	9.5
55	78	12	28	47	7	42	60	8	55	72	8	80	100	8
60	82	12	30	40	8	42	62	12	55	78	8	85	110	10
65	90	13	30	45	7	42	65	10	57	86	11	90	110	12
70	95	13	30	50	8	43	62	8	58	75	8	95	120	13
75	100	13	30	52	7	45	60	6	58	80	8	100	120	10
80	105	13	31	54	9.8	45	60	10	59	75	8	100	125	13
90	115	13	32	47	10	45	62	8	60	73	8	125	150	10
100	125	13	32.5	50.7	8.6	45	65	7	60	75	7	125	150	12
105	135	14	35	47	7	45	65	10	60	80	8	130	160	16
130	160	14	35	50	8	45	65	15	60	80	14	135	165	14
135	165	14	35	51	8	45	68	8	60	81.8	9	140	170	16
150	180	14	35	52	6	46	60	8	60	85	8	280	316	18
160	190	16	35	53	8	46	68	8	60	85	12			
10	25	7	35	60	10	47	62	15	60	90	10			
15	35	6	35	62	8	47.6	62	14.5	62	80	8			
15	42	6	36	51	8	48	62	8	62	85	8			
16	35	7	36	52	7	48	65	8	63	80	8			
17	35	7	38	51	7	48	70	10	65	80	8			
19	27	6	38	52	7	48	72	8	65	85	8			
19	40	7	38	55	10	50	60	8	65	85	12			
19	40	8	38	60	15	50	65	8	65	90	8			
20	35	8	38.5	62	8	50	68	10	68	90	10			
24	35.2	8	38	58	10	50	70	8	66.9	101.8	9.5			
25	40	7	39	55	10	50	70	10	70	85	8			

### 其他截面

