

F形四氟油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点
UP	F形四氟油封		四氟+弹簧	≤15	-70至260	≤2	耐高压, 耐磨. 清洁型

d	D	D1	L	d	D	D1	L	d	D	D1	L	d	D	D1	L
5	14	10	3.6	40	57.5	50.5	7.1	100	117.5	110.5	7.1	230	247.5	240.5	7.1
6	15	11	3.6	42	59.5	52.5	7.1	105	122.5	115.5	7.1	240	257.5	250.5	7.1
8	17	13	3.6	45	62.5	55.5	7.1	110	127.5	120.5	7.1	250	267.5	260.5	7.1
10	19	15	3.6	48	65.5	58.5	7.1	115	132.5	125.5	7.1	280	297.5	290.5	7.1
12	21	17	3.6	50	67.5	60.5	7.1	120	137.5	130.5	7.1	300	317.5	310.5	7.1
14	23	19	3.6	52	69.5	62.5	7.1	125	142.5	135.5	7.1	320	337.5	330.5	7.1
15	24	20	3.6	55	72.5	65.5	7.1	130	147.5	140.5	7.1	350	367.5	360.5	7.1
16	25	21	3.6	56	73.5	66.5	7.1	135	152.5	145.5	7.1	360	377.5	370.5	7.1
18	27	23	3.6	60	77.5	70.5	7.1	140	157.5	150.5	7.1	400	417.5	410.5	7.1
20	32.5	27	4.8	63	80.5	73.5	7.1	150	167.5	160.5	7.1	420	442	434	9.5
22	34.5	29	4.8	65	82.5	75.5	7.1	160	177.5	170.5	7.1	450	472	464	9.5
25	37.5	32	4.8	70	87.5	80.5	7.1	170	187.5	180.5	7.1	480	502	494	9.5
28	40.5	35	4.8	75	92.5	85.5	7.1	180	197.5	190.5	7.1	500	522	514	9.5
30	42.5	37	4.8	80	97.5	90.5	7.1	190	207.5	200.5	7.1	600	622	614	9.5
32	44.5	39	4.8	85	102.5	95.5	7.1	200	217.5	210.5	7.1	700	722	714	9.5
35	47.5	42	4.8	90	107.5	100.5	7.1	210	227.5	220.5	7.1				
36	48.5	43	4.8	95	112.5	105.5	7.1	220	237.5	230.5	7.1				